

ŞDP

**ŞAHİN DALGIÇ
MOTOR POMPA**



6" ŞDP SU SOĞUTMALI SARILABİLİR MOTORLAR

ŞDP 6" MOTOR

Eksenel Yük Taşıma Kapasitesi	5,5 HP - 30 HP : 20,0 kN
Axial Thrust Load Capacity	5,5 HP - 50 HP : 26,5 kN
Dış Çap / Outside Diameter	Ø 142 mm
Flanş Standardı / Flange Standart	6" NEMA Standart



Tip Type	PN		Eksenel Yük Axial Load kN	Voltaj voltage V	nN rpm	IN A	IA A	Verim (%yük) Efficiency (%load)			Cos Ø (%yük) Cos Ø (%load)		
	kW	HP						50	75	100	50	75	100
ŞDP 6" / 5,5	4	5,5	20	380	2770	10,2	39,4	67	71	76	63	71	86
				400	2785	9,8	37,8	68	72	78	59	69	82
				415	2795	9,5	36,9	68	72	78	57,5	70	81
ŞDP 6" / 7,5	5,5	7,5	20	380	2780	13,6	52,7	70	73	77	63	72	84
				400	2795	13,1	50,6	71	74	79	59	77	82
				415	2805	12,6	48,7	72	75	80	57,5	78	81
ŞDP 6" / 10	7,5	10	20	380	2790	17,2	66,4	77	79	79	63	72	84
				400	2805	16,5	63,8	79	80	80	59	70	82
				415	2815	16,1	62,2	79	80	80	57,5	71	81
ŞDP 6" / 12,5	9,3	12,5	20	380	2850	20,8	80,3	80	81	81	63	71	84
				400	2855	20,2	78,1	80	81	81	59	70	82
				415	2865	19,5	75,3	81	82	82	57,5	69	81
ŞDP 6" / 15	11	15	20	380	2810	23,7	91,6	81	82	82	67	73	86
				400	2825	22,8	88	82	83	83	63	69	84
				415	2835	22,2	85,9	82	83	83	61	70	83
ŞDP 6" / 17,5	13	17,5	20	380	2820	28,7	110,9	80	81	81	65	75	85
				400	2835	27,6	106,6	81	82	82	61	76	83
				415	2845	26,6	102,7	82	83	83	59	79	82
ŞDP 6" / 20	15	20	20	380	2850	33,1	127,9	80	81	81	65	73	85
				400	2855	32,2	124,5	80	81	81	61	69	83
				415	2865	31	120	81	82	82	59	67	82
ŞDP 6" / 25	18,5	25	26,5	380	2850	41,8	161,6	80	81	81	61	70	83
				400	2865	40,2	155,4	81	82	82	57,5	68	81
				415	2875	38,8	149,8	82	83	83	56,5	66	80
ŞDP 6" / 30	22	30	26,5	380	2860	48,5	187,6	81	82	82	63	71	84
				400	2875	46,7	180,3	82	83	83	59	69	82
				415	2885	45	173,9	83	84	84	57,5	65	81
ŞDP 6" / 35	26,5	35	26,5	380	2870	56,4	217,9	83	84	84	65	73	85
				400	2885	54,9	212	83	84	84	61	70	93
				415	2895	52,9	204,4	84	85	85	59	70	82
ŞDP 6" / 40	30	40	26,5	380	2880	64,6	249,7	82	83	83	65	73	85
				400	2895	62,1	240	83	84	84	61	68	83
				415	2905	59,9	231,4	84	85	85	59	67	82
ŞDP 6" / 50	37	50	26,5	380	2890	81,6	315,6	80	81	86	65	73	85
				400	2905	78,5	303,3	81	82	84	61	69	83
				415	2915	74,7	288,8	83	84	84	59	67	82



Tip Type	Ölçü Dimension	kW	HP	Direk D.O.L.		Yıldız Üçgen Wye - Delta		Eks Yük Ax. Thrust kN	Yol Verme Start start/h	Boy Lenght mm	Ağırlık Weight kg
				mm2	n	mm2	n				
ŞDP 6" / 5,5	6"	4	5,5	3x2,5	1	3x2,5	2	20	20	649	44
ŞDP 6" / 7,5	6"	5,5	7,5	3x2,5	1	3x2,5	2	20	20	678	47
ŞDP 6" / 10	6"	7,5	10	3x2,5	1	3x2,5	2	20	20	758	53
ŞDP 6" / 12,5	6"	9,3	12,5	3x2,5	1	3x2,5	2	20	20	800	57
ŞDP 6" / 15	6"	11	15	3x4	1	3x4	2	20	20	851	61
ŞDP 6" / 17,5	6"	13	17,5	3x4	1	3x4	2	20	20	911	66
ŞDP 6" / 20	6"	15	20	3x4	1	3x4	2	20	20	973	72
ŞDP 6" / 25	6"	18,5	25	3x4	1	3x4	2	20	20	1006	80
ŞDP 6" / 30	6"	22	30	3x6	1	3x6	2	20	20	1106	86
ŞDP 6" / 35	6"	26,5	35	3x6	1	3x6	2	26,5	20	1217	90
ŞDP 6" / 40	6"	30	40	3x10	1	3x10	2	26,5	20	1247	104
ŞDP 6" / 50	6"	37	50	3x10	1	3x10	2	26,5	15	1347	111

