



ŞAHİN DALGIÇ MOTOR POMPA



7" ŞDP SU SOĞUTMALI SARILABİLİR MOTORLAR

ŞDP 7" MOTOR

Eksenel Yük Taşıma Kapasitesi	30 HP - 75 HP : 25 kN
Axial Thrust Load Capacity	30 HP - 75 HP : 25 kN
Dış Çap / Outside Diameter	Ø 172 mm
Flaş Standardı / Flange Standart	6" NEMA Standart



Tip Type	PN		Eksenel Yük Axial Load kN	Voltaj voltage V	nN rpm	IN A	IA A	Verim (%yük) Efficiency (%load)			Cos Ø (%yük) Cos Ø (%load)		
	kW	HP						50	75	100	50	75	100
ŞDP 7" / 30	22	30	45	380	2880	46	235	83	84	84	76	82	86
				400	2900	44	225	82	84	85	75	81	85
				415	2910	43	219	81	84	85	70	77	83
ŞDP 7" / 35	26,5	35	45	380	2880	55	279	84	85	85	66	75	86
				400	2900	53	269	83	85	85	63	74	85
				415	2910	52	262	82	85	86	61	72	83
ŞDP 7" / 40	30	40	45	380	2880	62	312	85	86	85	65	74	86
				400	2900	59	300	84	86	86	63	73	85
				415	2910	58	294	83	86	87	61	71	83
ŞDP 7" / 50	37	50	45	380	2880	74	377	85	86	86	78	85	88
				400	2900	72	366	84	86	86	75	82	86
				415	2910	70	258	83	86	87	71	80	84
ŞDP 7" / 60	45	60	45	380	2870	90	459	85	86	86	76	84	88
				400	2890	88	446	84	86	86	76	83	86
				415	2900	86	435	83	86	87	74	80	84
ŞDP 7" / 70	52	70	45	380	2860	106	537	85	86	86	78	83	87
				400	2880	103	522	85	86	86	76	82	85
				415	2890	100	509	84	86	87	73	79	83
ŞDP 7" / 75	55	75	45	380	2900	109	554	85	85	84	70	84	88
				400	2905	106	540	84	85	84	78	83	86
				415	2910	103	518	83	85	85	77	80	84



Tip Type	Ölçü Dimension	kW	HP	Direk D.O.L.		Yıldız Üçgen Wye - Delta		Eks Yük Ax. Thrust kN	Yol Verme Start start/h	Boy Lenght mm	Ağırlık Weight kg
				mm2	n	mm2	n				
ŞDP 7" / 30	7"	22	30	3x10	1	3x10	2	45	17	890	105
ŞDP 7" / 35	7"	26,5	35	3x10	1	3x10	2	45	17	940	110
ŞDP 7" / 40	7"	30	40	3x10	1	3x10	2	45	17	980	117
ŞDP 7" / 50	7"	37	50	3x10	1	3x10	2	45	17	1060	127
ŞDP 7" / 60	7"	45	60	3x16	1	3x16	2	45	17	1139	142
ŞDP 7" / 70	7"	52	70	3x16	1	3x16	2	45	17	1218	153
ŞDP 7" / 75	7"	55	75	3x16	1	3x16	2	45	17	1250	160

