



# ŞAHİN DALGIÇ MOTOR POMPA



## 10" ŞDP SU SOĞUTMALI SARILABİLİR MOTORLAR

### ŞDP 10" MOTOR

Eksenel Yük Taşıma Kapasitesi	125 HP - 250 HP : 75 kN
Axial Thrust Load Capacity	125 HP - 250 HP : 75 kN
Dış Çap / Outside Diameter	Ø 231 mm
Flanş Standardı / Flange Standart	8" NEMA Standart



Tip Type	PN		Eksenel Yük Axial Load kN	Voltaj voltage V	nN rpm	IN A	IA A	Verim (%yük) Efficiency (%load)			Cos Ø (%yük) Cos Ø (%load)		
	kW	HP						50	75	100	50	75	100
ŞDP 10" / 110	81	110	75	380	2880	159	615	84	85	85	78,5	84	91
				400	2895	153	590	85	86	86	74,5	80	89
				415	2905	147	569	86	87	87	71,5	78	88
ŞDP 10" / 125	92	125	75	380	2890	179	690	85	86	86	78,5	84	91
				400	2905	174	671	85	86	86	74,5	80	89
				415	2915	169	654	85	86	86	71,5	78	88
ŞDP 10" / 150	110	150	75	380	2890	216	835	85	86	86	77	83	90
				400	2905	210	811	85	86	86	71,5	78	88
				415	2915	205	790	85	86	86	68,5	76	87
ŞDP 10" / 175	129	175	75	380	2910	248	957	86	87	87	78,5	84	91
				400	2925	238	919	87	88	88	74,5	80	89
				415	2935	232	896	87	88	88	71,5	78	88
ŞDP 10" / 200	147	200	75	380	2900	282	1090	86	87	87	78,5	84	91
				400	2915	274	1059	86	87	87	74,5	80	89
				415	2925	264	1020	87	88	88	71,5	78	88
ŞDP 10" / 225	166	225	75	380	2890	322	1245	85	86	86	78,5	84	91
				400	2905	309	1196	86	87	87	74,5	80	89
				415	2915	302	1165	86	87	87	71,5	78	88
ŞDP 10" / 250	185	250	75	380	2895	359	1388	85	86	86	78,5	84	91
				400	2905	349	1348	85	86	86	74,5	80	89
				415	2915	336	1299	86	87	87	71,5	78	88



Tip Type	Ölçü Dimension	kW	HP	Direk D.O.L.		Yıldız Üçgen Wye - Delta		Eks Yük Ax. Thrust kN	Yol Verme Start start/h	Boy Lenght mm	Ağırlık Weight kg
				mm2	n	mm2	n				
ŞDP 10" / 110	10"	81	110	3x25	1	3x25	2	75	10	1370	255
ŞDP 10" / 125	10"	92	125	3x25	1	3x25	2	75	10	1430	274
ŞDP 10" / 150	10"	110	150	3x25	1	3x25	2	75	10	1510	299
ŞDP 10" / 175	10"	129	175	3x25	1	3x25	2	75	10	1610	328
ŞDP 10" / 200	10"	147	200	3x25	1	3x25	2	75	10	1740	368
ŞDP 10" / 225	10"	166	225	3x25	1	3x25	2	75	10	1820	402
ŞDP 10" / 250	10"	185	250	3x25	1	3x25	2	75	10	1820	436

