



ŞAHİN DALGIÇ MOTOR POMPA

KOMPLE PASLANMAZ ÇELİK KAPALI FANLI SANTRİFÜJ POMPALAR



KOMPLE PASLANMAZ ÇELİK KAPALI FANLI SANTRİFÜJ POMPALAR - STAINLESS STEEL CLOSE IMPELLER CENTRIFUGAL PUMPS

Pompa Model Pump Model	Güç Power			Pompa Pump Bore		Basılan Su (Debi)						
	Hp	Kw	V	Giriş Suction	Çıkış Delivery	Q (m³ / saat)						
						0	6	12	18	24	30	36
ŞDP 1014 (304)	1	0,75	380	1 1/2"	1 1/2"	16	14,5	13	10	6		
ŞDP 1015 (304)	1	0,75	220	1 1/2"	1 1/2"	16	14,5	13	10	6		
ŞDP 1016 (304)	1,5	1,1	220	2"	2"	20	18,5	16,5	13,5	9,5		
ŞDP 1017 (304)	1,5	1,1	380	2"	2"	20	18,5	16,5	13,5	9,5		
ŞDP 1018 (304)	2	1,5	220	2"	2"	24	22,5	20,5	17,5	13,5		
ŞDP 1019 (304)	2	1,5	380	2"	2"	24	22,5	20,5	17,5	13,5		
ŞDP 1020 (304)	3	2,2	380	2"	2"	23	22	21,5	20	18,5	16,5	14,5
ŞDP 1021 (304)	4	3	380	2"	2"	25	23	24	22,5	21	19	17

- Maksimum ortam sıcaklığı +40 °C
- Maksimum su sıcaklığı +80 °C
- Maksimum emiş 6-7 metre
- Paslanmaz çelik fan ve pompa gövdesi
- Motor izolasyon sınıfı F classtr
- Sessiz çalışır
- 220 Volt pompalar termik korumalıdır
- Su ile temas eden tüm yüzeyler paslanmaz çeliktir
- Pompa ağırlığı ŞDP 1014 11,2 kg ,1015 16 kg, 1016 17 kg, 1017 22,5 kg, 1018-1021 24,5 kg

- Maximum ambient temperature +40 °C
- Maximum liquid temperature up to +80 °C
- Maximum suction lift up to 6-7 meter
- Stainless steel impeller , pump casing
- Insulation class F
- Low noise
- 220 Volt pumps are thermal protected
- All surfaces contacted with water are made of stainless steel
- Pompa weight ŞDP 1014 11,2 kg ,1015 16 kg, 1016 17 kg, 1017 22,5 kg, 1018-1021 24,5 kg

