



# ŞAHİN DALGIÇ MOTOR POMPA



## DÖKÜM GÖVDELİ YÜKSEK DEBİLİ ATIK SU POMPALARI - 1450 d/dk CAST - IRON HIGH FLOW SEWAGE PUMPS - 1450 rpm

| Pompa Model<br>Pump Model | Güç Power |    |     | Pompa Power Bore  |                   | Basılan Su (Debi)           |     |     |     |     |     |
|---------------------------|-----------|----|-----|-------------------|-------------------|-----------------------------|-----|-----|-----|-----|-----|
|                           | Hp        | Kw | V   | Ağırlık<br>Weight | Çıkış<br>Delivery | Q ( m <sup>3</sup> / saat ) |     |     |     |     |     |
|                           |           |    |     |                   |                   | 70                          | 150 | 200 | 250 | 360 | 510 |
| ŞDP WQ 146                | 15        | 11 | 380 | 274               | 6"                | 19                          | 15  | 14  | 9   |     |     |
| ŞDP WQ 147                | 20        | 15 | 380 | 295               | 6"                | 24                          | 20  | 18  | 15  |     |     |
| ŞDP WQ 151                | 30        | 22 | 380 | 367               | 6"                | 33                          | 28  | 25  | 22  | 13  |     |
| ŞDP WQ 152                | 40        | 30 | 380 | 549               | 8"                | 31                          | 28  | 26  | 24  | 19  | 10  |

- Maksimum daldırma derinliği : 8 metre
- Döküm kapalı tip geniş fanlı
- Maksimum partikül çapı : 70 mm
- 1450 d / dk 4 kutupludur

- The maximum immersion depth : 8 m
- Cast iron close type large impeller
- Maximum solid passage : 70 mm
- Motor speed 1450 rpm 4 poles