



# ŞAHİN DALGIÇ MOTOR POMPA

## PASLANMAZ DİK MİLLİ IN LINE POMPALARI

### KOMPLE PASLANMAZ ÇELİK , DİK MİLLİ IN LINE POMPALAR - STAINLESS STEEL MULTISTAGE VERTICAL PUMPS WITH IN - LINE BORES

Pompa Model Pump Model	Güç Power			Pompa Pump Bore		Debi ( ton/saat )						
	Hp	Kw	V	Giriş Suction	Çıkış Delivery	Flow ( m <sup>3</sup> / saat )						
						1,2	2	2,4	3	3,2	3,8	4
						Basma Yüksekliği (Hm) mss						
ŞDP CV3-10 1040	1	0,75	220	1"	1"	59	55	51	43	41	34	28
ŞDP CV3-10T 1041	1	0,75	380	1"	1"	59	55	51	43	41	34	28
ŞDP CV3-12 1042	1,5	1,1	220	1"	1"	71	66	61	52	49	42	34
ŞDP CV3-12T 1043	1,5	1,1	380	1"	1"	71	66	61	52	49	42	34
ŞDP CV3-15T 1044	1,5	1,1	380	1"	1"	88	82	77	69	64	55	44
ŞDP CV3-19T 1045	2	1,5	380	1"	1"	112	104	98	88	83	71	58
ŞDP CV3-21T 1046	3	2,2	380	1"	1"	123	115	108	97	92	79	65
ŞDP CV3-25T 1047	3	2,2	380	1"	1"	146	135	128	113	108	94	79
						0	2	4	5	6	7	8
ŞDP CV5-10 1050	2	1,5	220	1 1/4"	1 1/4"	66	62	55	50	44	37	30
ŞDP CV5-10T 1051	2	1,5	380	1 1/4"	1 1/4"	66	62	55	50	44	37	30
ŞDP CV5-14 1065	3	2,2	220	1 1/4"	1 1/4"	94	89	81	74	65	54	42
ŞDP CV5-14T 1052	3	2,2	380	1 1/4"	1 1/4"	94	89	81	74	65	54	42
ŞDP CV5-16T 1053	3	2,2	380	1 1/4"	1 1/4"	108	103	94	85	75	63	48
ŞDP CV5-20T 1054	4	3	380	1 1/4"	1 1/4"	132	129	115	105	94	78	60
						0	4	6	8	10	12	14
ŞDP CV10-6T 1055	3	2,2	380	2"	2"	64	61	58	53	46	38	28
ŞDP CV10-9T 1056	4	3	380	2"	2"	96	91	87	81	71	59	42
ŞDP CV10-12T 1057	5,5	4	380	2"	2"	126	121	117	108	95	78	55
ŞDP CV10-14T 1058	7,5	5,5	380	2"	2"	146	141	136	124	110	90	63
						8	12	14	16	18	20	24
ŞDP CV15-5 1062	5,5	4	380	2"	2"	66	61	58	54	50	45	33
ŞDP CV15-6 1063	7,5	5,5	380	2"	2"	80	75	70	65	60	54	41
ŞDP CV15-7 1059	7,5	5,5	380	2"	2"	94	88	83	78	71	64	50
ŞDP CV15-9 1060	10	7,5	380	2"	2"	122	115	109	103	95	87	66
ŞDP CV15-12 1064	15	11	380	2"	2"	158	150	144	135	126	116	89
						12	20	24	28	30	32	40
ŞDP CV32-4T 1070	10	7,5	380	3"	3"	72	66	62	56	53	50	34
ŞDP CV32-6T1071	15	11	380	3"	3"	109	101	95	87	83	77	52



- Maksimum su sıcaklığı +80 °C  
-Maksimum emiş : 4 metre  
- Paslanmaz çelik fan ve difüzör  
- Su ile temas eden tüm yüzeyler paslanmaz çeliktir

- Maximum liquid temperature up to : +80 °C  
-Maximum suction lift up to : 4 m  
-Stainless steel impeller,diffuser  
-All surfaces contacted with water are made of stainless steel