



ŞAHİN DALGIÇ
MOTOR POMPA

NORYL FANLI TEK POMPALI PAKET HİDROFORLAR



TEK POMPALI PAKET HİDROFORLAR - BOOSTER SETS WITH ONE MULTISTAGE VERTICAL PUMPS

Pompa Model Pump Model	Güç Power			Pompa Pump Bore		Debi (ton/saat)							Kat Daire Storey Apartmans
	Hp	Kw	V	Giriş Suction	Çıkış Delivery	Flow (m ³ / saat)							
						0	1,2	3,6	4,8	6	6,6	7,2	
ŞDP 1YMPV6-60 341	1,5	1,1	220	1 1/4"	1"	65	55	45	38	24	14		6K - 12D
ŞDP 1YMPV6-80 342	2	1,5	220	1 1/4"	1"	80	72	55	45	30	16		8K - 16D
ŞDP 1YMPV6-80 340	3	2,2	380	1 1/4"	1"	80	72	55	45	30	16		8K - 16D
ŞDP 1YMPV6-90 339	5	3,7	380	1 1/4"	1"	90	75	60	50	32	18		10K - 16D
ŞDP 1YMPV9-80 344	2	1,5	380	1 1/2"	1 1/4"	85	76	70	60	46	42	35	8K - 24D
ŞDP 1YMPV9-90 345	3	2,2	380	1 1/2"	1 1/4"	95	85	75	65	50	47	40	9K - 24D

- Fiyatlarımıza hidrofor tankı ve flex hortum dahil değildir
- Sehpa,küresel vana,5 yollu çekvalf,manometre,basınç,şalteri,hidrofor,kumanda panosu,baplanlı ekipmanları ve 5 metre flatör fiyatlara dahildir.
- Maksimum su sıcaklığı +40 °C
- Maksimum emiş : 4 metre
- Noril fanlı
- Mili paslanmaz çeliktir
- Sessiz çalışır
- 220 Volt pompalar termik korumalıdır

- Pressure tank and flexible hose are not included to the prices
- Table,ball valve,5 way check valve,presure gauge and switch control box,fittings and 5 mt. Float switch are included.
- Maximum liquid temperature up to: +40 °C
- Maximum suction lift up to : 4 m
- Noryl impeller
- Stainless steel welding shaft
- Low noise
- 220 Volt pumps are thermal protected